

# K-MANO

Pressure gauges (CrNi steel type / connection on rear)

**HANSA FLEX**

## Properties

<b>Type</b>	232.50
<b>Design</b>	Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel
<b>Application</b>	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
<b>Accuracy class</b>	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
<b>Media temperature</b>	max. +200 °C
<b>Ambient temperature</b>	-40 °C to +60 °C
<b>Housing</b>	CrNi steel
<b>Inspection glass</b>	Laminated safety glass Ø 63 = Polycarbonate



## Note

Further information on request

## Item

Identification	Measuring range	Ø (mm)	Connection
K- 07 20 06 10	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 06 11	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 06 12	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 06 13	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 06 14	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 06 15	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 06 16	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 06 17	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 06 18	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 06 19	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 00 53	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 54	0 - 10.0 bar	100,0	G 1/2"