

# K-KFMM U MBAR 10FACH UEBERLASTUNG

Capsule-type pressure gauges for measuring pressure in millibars

**HANSA FLEX**

## Properties

Type	611.10 (Ø 63), 612.20 (Ø 100)
Design	Capsule-type pressure gauge
Application	For gaseous, dry, non-corrosive media
Accuracy class	1,6
Media temperature	max. +100 °C
Ambient temperature	-20 °C to +60 °C
Housing	Steel, black (Ø 63 mm)CrNi steel (Ø 100 mm)
Measuring element and movement	Copper alloy
Inspection glass	Plexiglass



## Note

Further information on request

## Description

Overpressure safety 10x FSD, with zero correction

## Item

Identification	Measuring range	Ø (mm)	Connection
K- 07 20 06 83	0 - 40 mbar	63,0	G 1/4"
K- 07 20 06 84	0 - 60 mbar	63,0	G 1/4"
K- 07 20 06 85	0 - 100 mbar	63,0	G 1/4"
K- 07 20 06 86	0 - 160 mbar	63,0	G 1/4"
K- 07 20 06 87	0 - 250 mbar	63,0	G 1/4"
K- 07 20 01 08	0 - 40 mbar	100,0	G 1/2"
K- 07 20 01 09	0 - 60 mbar	100,0	G 1/2"
K- 07 20 01 10	0 - 100 mbar	100,0	G 1/2"
K- 07 20 01 11	0 - 160 mbar	100,0	G 1/2"
K- 07 20 01 12	0 - 250 mbar	100,0	G 1/2"