

K-MANO ROB U

Robust pressure gauges, connection radial on bottom

HANSA FLEX

Properties

| | |
|---------------------|--|
| Type | 212.20 |
| Design | Robust Bourdon-tube pressure gauge |
| Application | For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise |
| Accuracy class | 1,0 |
| Media temperature | max. +80 °C |
| Ambient temperature | -40 °C to +60 °C |
| Housing | CrNi steel |
| Measuring element | Copper alloy (≤ 100 bar), CrNi steel (> 100 bar) |
| Inspection glass | Flat instrument glass |
| Movement | Copper alloy |



Note

Further information on request

Additional information

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Item

| Identification | Measuring range | Ø (mm) | Connection |
|----------------|-----------------|--------|------------|
| K- 07 20 01 44 | -1 / 0.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 45 | -1 / +1.5 bar | 100,0 | G 1/2" |
| K- 07 20 01 46 | -1 / +3.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 47 | -1 / +5.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 48 | -1 / +9.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 49 | -1 / +15.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 50 | 0 - 0.6 bar | 100,0 | G 1/2" |
| K- 07 20 01 51 | 0 - 1.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 52 | 0 - 1.6 bar | 100,0 | G 1/2" |
| K- 07 20 01 53 | 0 - 2.5 bar | 100,0 | G 1/2" |
| K- 07 20 01 54 | 0 - 4.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 55 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 56 | 0 - 10.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 57 | 0 - 16.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 58 | 0 - 25.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 59 | 0 - 40.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 60 | 0 - 60.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 61 | 0 - 100.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 62 | 0 - 160.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 63 | 0 - 250.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 64 | 0 - 400.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 65 | 0 - 600.0 bar | 100,0 | G 1/2" |
| K- 07 20 01 66 | 0 - 1000.0 bar | 100,0 | G 1/2" |
| K- 07 20 03 24 | -1 / 0.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 25 | 0 - 0.6 bar | 160,0 | G 1/2" |
| K- 07 20 03 26 | 0 - 1.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 27 | 0 - 1.6 bar | 160,0 | G 1/2" |
| K- 07 20 03 28 | 0 - 2.5 bar | 160,0 | G 1/2" |
| K- 07 20 03 29 | 0 - 4.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 30 | 0 - 6.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 31 | 0 - 10.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 32 | 0 - 16.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 33 | 0 - 25.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 34 | 0 - 40.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 35 | 0 - 60.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 36 | 0 - 100.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 37 | 0 - 160.0 bar | 160,0 | G 1/2" |



Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.

26.04.2026

HANSA-FLEX AG

www.hansa-flex.com

K-MANO ROB U

Robust pressure gauges, connection radial on bottom

Item

| Identification | Measuring range | Ø (mm) | Connection |
|----------------|-----------------|-----------|------------|
| K- 07 20 03 38 | 0 - 250.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 39 | 0 - 400.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 40 | 0 - 600.0 bar | 160,0 | G 1/2" |