


Properties

Application	For all pressure gauges with a flat gasket acc. to DIN 16258
Pressure range	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
Temperature	Max. +50 °C
Housing	Brass with a bare metal surface or stainless steel 1.4571
Handle	Plastic
Test flange	-



Note

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Further information on request

Description

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Additional information

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Item	Identification	Thread	PN (bar)	AF (mm)	Material
K-07 20 10 94		G 1/4	6	17	Brass
K-07 20 10 95		G 3/8	16	22	Brass
K-07 20 10 97		G 1/2	25	27	Brass
K-07 20 10 96		G 1/2	25	27	Stainless steel
K-07 20 10 98		G 1/2	25	27	Brass