

# K-MANO ABSPV ZAPF DREH MUF 16270B

Pressure gauge valves, male - loose female connector and shaft for instrument holder, DIN 16270

**HANSA*****FLEX***

## Properties

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| Operating pressure        | max. 250 bar brass, max. 400 bar steel/<br>stainless steel         |
| Temperature               | Max. +120 °C with brass/steel; Max. +200 °C<br>for stainless steel |
| material all components   | Stainless steel                                                    |
| Sealant                   | PTFE                                                               |
| Housing                   | Brass, black-finished steel or stainless steel<br>1.4571           |
| Handwheel                 | Plastic                                                            |
| Union nut clamping sleeve | Steel                                                              |
| Valve spindle, valve cone | Stainless steel                                                    |



## Note

Further information on request

## Description

They are used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

## Item

| Identification | Thread | PN (bar) | AF<br>(mm) | Material        |
|----------------|--------|----------|------------|-----------------|
| K- 07 20 11 16 | G 1/2  | 250      | 27         | Brass           |
| K- 07 20 11 15 | G 1/2  | 400      | 27         | Stainless steel |