K-MANO SCHW

Pressure gauges for welding

Properties

Type	111.11
Design	Bourdon-tube pressure gauge acc. to EN 562
Application	For welding systems and cutting machines or similar processes
Accuracy class	2,5
Media temperature	max. +60 °C
Ambient temperature	-40 °C to +60 °C
Housing	Steel, brass-coloured
Measuring element and movement	Copper alloy
Inspection glass	Polycarbonate



Note

Further information on request

Item

Identification	Measuring range	Ø (mm)	Marking	Connection
K- 07 20 11 08	0 - 16.0 bar	63,0	oxygen	G 1/4
K- 07 20 11 10	0 - 315.0 bar	63,0	oxygen	G 1/4
K- 07 20 11 12	0 - 2.5 bar	63,0	acetylene	G 1/4
K- 07 20 11 13	0 - 40.0 bar	63,0	acetylene	G 1/4

Spare part for following products

K-FLASCHENDRUCKR 200 N GASE	Cylinder pressure regulators, cylinder pressure 200 bar, for non-flammable gases
K-FLASCHENDRUCKR 200 GASE	Cylinder pressure regulators, cylinder pressure 200 bar, for flammable gases
K-FLASCHENDRUCKR 300 N GASE	Cylinder pressure regulators, cylinder pressure 300 bar, for non-flammable gases
K-FLASCHENDRUCKR 300 GASE	Cylinder pressure regulators, cylinder pressure 300 bar, for flammable gases

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.