

# K-RMM U KUNSTSTOFF

Standard pressure gauges (pastic housing / connection radial on bottom)

**HANSA FLEX**

## Properties

Type	111.10
Design	Bourdon-tube pressure gauge in standard design
Application	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Accuracy class	1.6 (Art. No. K-07200454: 2.5)
Media temperature	max. +60 °C
Ambient temperature	-20 °C to +60 °C
Housing	Plastic
Measuring element and movement	Copper alloy
Inspection glass	Transparent plastic



## Note

Further information on request

## Item

Identification	Measuring range	Ø (mm)	Connection
K- 07 20 04 47	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 48	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 49	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 50	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 51	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 52	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 53	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 54	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 55	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 51	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 52	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 53	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 54	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 55	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 56	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 57	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 58	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 59	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 60	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 61	0 - 100.0 bar	50,0	G 1/4
K- 07 20 05 62	0 - 160.0 bar	50,0	G 1/4
K- 07 20 05 63	0 - 60.0 bar	50,0	G 1/4