

K-RMM U STAHL

Standard pressure gauges (sheet steel housing / connection radial on bottom)

HANSA FLEX

Properties

Type	111.10
Design	Bourdon-tube pressure gauge in standard design
Application	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Accuracy class	1.6 (Art. No. K-07200581: 2.5)
Media temperature	max. +60 °C
Ambient temperature	-20 °C to +60 °C
Housing	Sheet steel
Measuring element and movement	Copper alloy
Inspection glass	Transparent plastic



Note

Further information on request

Item

Identification	Measuring range	Ø (mm)	Connection
K- 07 20 04 65	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 66	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 67	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 68	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 69	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 70	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 71	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 72	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 73	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 76	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 77	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 78	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 79	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 80	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 81	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 82	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 83	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 84	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 85	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 86	0 - 60.0 bar	50,0	G 1/4
K- 07 20 05 87	0 - 100.0 bar	50,0	G 1/4
K- 07 20 05 88	0 - 160.0 bar	50,0	G 1/4