

K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

Properties

Operating temperature	-60 °C to +100 °C (PA 12)
Properties	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Pipe length	3 m
Packaging unit	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Material	Polyamid PA 12, hard (according to DIN 73378)



Note

Operating pressure with 2.5 x overpressure safety!
Further information on request

Description

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Item

Identification	External pipe Ø (mm)	Internal pipe Ø (mm)	max. working pressure at 20° C (bar)	Colour
K- 07 10 04 57	12	9	38	blue
K- 07 10 04 59	12	9	38	black
K- 07 10 04 61	15	12	25	blue
K- 07 10 04 63	15	12	25	black
K- 07 10 04 65	18	14	28	blue
K- 07 10 04 67	18	14	28	black
K- 07 10 04 69	22	18	22	blue
K- 07 10 04 71	22	18	22	black
K- 07 10 04 73	28	23	20	blue
K- 07 10 04 75	28	23	20	black