

K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

HANSA FLEX

Properties

| | |
|-----------------------|---|
| Operating temperature | -60 °C to +100 °C (PA 12) |
| Properties | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| Pipe length | 3 m |
| Packaging unit | 10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units! |
| Material | Polyamid PA 12, hard (according to DIN 73378) |



Note

Operating pressure with 2.5 x overpressure safety!

Further information on request

Description

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

| Item | | | | |
|----------------|-------------------------|-------------------------|---|--------|
| Identification | External pipe Ø (mm) | Internal pipe Ø (mm) | max. working pressure at 20° C (bar) | Colour |
| K- 07 10 04 57 | 12 | 9 | 38 | blue |
| K- 07 10 04 59 | 12 | 9 | 38 | black |
| K- 07 10 04 61 | 15 | 12 | 25 | blue |
| K- 07 10 04 63 | 15 | 12 | 25 | black |
| K- 07 10 04 65 | 18 | 14 | 28 | blue |
| K- 07 10 04 67 | 18 | 14 | 28 | black |
| K- 07 10 04 69 | 22 | 18 | 22 | blue |
| K- 07 10 04 71 | 22 | 18 | 22 | black |
| K- 07 10 04 73 | 28 | 23 | 20 | blue |
| K- 07 10 04 75 | 28 | 23 | 20 | black |