

Properties				
Operating temperature	-60 °C to +100 °C (PA 12)			
Properties	Resistant to corrosion, vibration, impact, ageing, high pressures and heat			
Pipe length	3 m			
Packaging unit	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!			
Material	Polyamid PA 12, hard (according to DIN 73378)			



Note

Operating pressure with 2.5 x overpressure safety! Further information on request

Description

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Item					
Identification	External pipe Ø	Internal pipe Ø	max. working pressure at 20° C	Colour	
K- 07 10 04 57	12	9	38	blue	
K- 07 10 04 59	12	9	38	black	
K- 07 10 04 61	15	12	25	blue	
K- 07 10 04 63	15	12	25	black	
K- 07 10 04 65	18	14	28	blue	
K- 07 10 04 67	18	14	28	black	
K- 07 10 04 69	22	18	22	blue	
K- 07 10 04 71	22	18	22	black	
K- 07 10 04 73	28	23	20	blue	
K- 07 10 04 75	28	23	20	black	