

# K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

## Properties

<b>Operating temperature</b>	-60 °C to +100 °C (PA 12)
<b>Properties</b>	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
<b>Pipe length</b>	3 m
<b>Packaging unit</b>	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
<b>Material</b>	Polyamid PA 12, hard (according to DIN 73378)



## Note

Operating pressure with 2.5 x overpressure safety!  
Further information on request

## Description

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Item

Identification	External pipe Ø (mm)	Internal pipe Ø (mm)	max. working pressure at 20° C (bar)	Colour
K- 07 10 04 56	12	9	38	blue
K- 07 10 04 58	12	9	38	black
K- 07 10 04 60	15	12	25	blue
K- 07 10 04 62	15	12	25	black
K- 07 10 04 64	18	14	28	blue
K- 07 10 04 66	18	14	28	black
K- 07 10 04 68	22	18	22	blue
K- 07 10 04 70	22	18	22	black
K- 07 10 04 72	28	23	20	blue
K- 07 10 04 74	28	23	20	black