

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Properties

Operating temperature	-60 °C to +100 °C (PA 12)
Properties	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Pipe length	3 m
Packaging unit	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Material	Polyamid PA 12, hard (according to DIN 73378)



Note

Operating pressure with 2.5 x overpressure safety!
Further information on request

Description

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Item

Identification	External pipe Ø (mm)	Internal pipe Ø (mm)	max. working pressure at 20° C (bar)	Colour
K- 07 10 04 56	12	9	38	blue
K- 07 10 04 58	12	9	38	black
K- 07 10 04 60	15	12	25	blue
K- 07 10 04 62	15	12	25	black
K- 07 10 04 64	18	14	28	blue
K- 07 10 04 66	18	14	28	black
K- 07 10 04 68	22	18	22	blue
K- 07 10 04 70	22	18	22	black
K- 07 10 04 72	28	23	20	blue
K- 07 10 04 74	28	23	20	black