K-SCHL-AUFROLLER LUFT


Hose reels for compressed air

HANSA/FLEX

Properties

| Hose material | Braided polyurethane Max. 16 bar; 13.5 x 9.5 mm hose: max. 12 bar | | | | |
|-----------------------|--|--|--|--|--|
| Operating pressure | Max. 16 bar; 13.5 x 9.5 mm hose: max. 12 bar | | | | |
| Operating temperature | -20 °C to +60 °C | | | | |
| Swivel angle | 300° | | | | |





Note

Further information on request

Description

For easy mounting on the wall or ceiling. Closed, rugged, impact-resistant housing made of POM, supply/outlet R 1/4 male thread and lightweight, hard-wearing, oil-resistant polyurethane hose. Incl. 2 m feeder hose (not Art. K-07100618).

Additional information

Housing of K-07100621, K-07100620 and K-07100618 identical to K-07100614

| Item | | | | | |
|----------------|------------------|-------|-------|-------------|--|
| Identification | Hose size | А | В | Hose lenght | |
| | | (mm) | (mm) | (m) | |
| K- 07 10 06 18 | 12 mm x 8 mm | 394,5 | 436,0 | 7 | |
| K- 07 10 06 19 | 12 mm x 8 mm | 361,0 | 390,0 | 10 | |
| K- 07 10 06 20 | 12 mm x 8 mm | 394,5 | 436,0 | 16 | |
| K- 07 10 06 21 | 13,5 mm x 9,5 mm | 394,5 | 436,0 | 14 | |