K-SPIR SCHL

Spiral hose, without fittings

Properties

Application	Air, gases, oils, greases, fuels, organic and inorganic substances
Operating temperature	-40 °C to +100 °C



Note

Further information on request

Description

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Item

Identification	Ø hose internal (mm)	Ø hose external (mm)	Ø spiral external (mm)	coils	Max. working pressure resistance at 23°C (bar)	max. working length (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

Accessories

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.