K-SPIR SCHL DREH VERSCHRAU

Spiral hose, with swivel adapter and kink protector

HANSA-FLEX

Properties

Operating temperature	-40 °C to +74 °C



Note

Further information on request

Description

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Item

Identification	Thread	Ø hose internal (mm)	Ø hose external (mm)	Ø external coil (mm)	Max. working pressure resistance at 23°C (bar)	max. working length (m)
K- 07 10 07 19	G 1/4	5,0	8,0	40	10	3,0
K- 07 10 07 20	G 1/4	5,0	8,0	40	10	6,0
K- 07 10 07 21	G 1/4	5,0	8,0	40	10	7,5
K- 07 10 07 22	G 1/4	6,3	9,5	60	10	3,0
K- 07 10 07 23	G 1/4	6,3	9,5	60	10	6,0
K- 07 10 07 24	G 1/4	6,3	9,5	60	10	7,5
K- 07 10 12 77	G 1/4	6,3	9,5	60	10	10,0
K- 07 10 07 25	G 3/8	8,0	12,0	80	9	3,0
K- 07 10 07 26	G 3/8	8,0	12,0	80	9	6,0
K- 07 10 07 27	G 3/8	8,0	12,0	80	9	7,5
K- 07 10 12 86	G 3/8	8,0	12,0	80	9	10,0

Accessories

K-DREHBARE VERSCHRAUBUNG	Swivel adapters

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.