

K-VSEH AIRKRAFT

Receptacle combinations »airkraft«

Properties

| | |
|----------------------------------|---|
| Housing | Amaplast with hinged cover |
| Integrated in the housing | Hanging eyelets, wall mounting fixing and standing feet |
| Fusing | Beneath transparent lid (4 MW) |
| Design | Pre-wired |
| Cable entries | Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out) |
| Protection IP | IP 44 |



Note

Further information on request

Description

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Item

| Identification | Parts included | Colour |
|----------------|---|--------|
| K- 07 10 03 52 | 4 Schuko socket 16 A 2p + E 230 V | yellow |
| K- 07 10 03 51 | 3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V | silver |

Accessories

| | |
|--------------------------------------|--|
| K-VT 2 KUPPL 7,2 STECKNIP MS | Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8 |
| K-ZUBEH VSEH 3 KRAFT AIRKRAFT | Accessories for receptacle combinations »3-Kraft« and »airkraft« |