K-VSEH AIRKRAFT

Receptacle combinations »airkraft«

Properties

Housing	Amaplast with hinged cover
Integrated in the housing	Hanging eyelets, wall mounting fixing and standing feet
Fusing	Beneath transparent lid (4 MW)
Design	Pre-wired
Cable entries	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
Protection IP	IP 44



Note

Further information on request

Description

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Item

Identification	Parts included	Colour
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	yellow
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	silver

Accessories

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.