# K-VSEH AIRKRAFT

## Receptacle combinations »airkraft«



Properties	
Housing	Amaplast with hinged cover
Integrated in the housing	Hanging eyelets, wall mounting fixing and standing feet
Fusing	Beneath transparent lid (4 MW)
Design	Pre-wired
Cable entries	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
Protection IP	IP 44



#### Note

Further information on request

### Description

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

#### Item

Identification	Parts included	Colour
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	yellow
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	silver

Accessories	
K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«