## K-HYDR-KUPPLUNG IG MS

Hydraulic couplings, brass



Properties					
Operating pressure	ee table. All values referred to a medium mperature of 50 °C (static working pressure)				
Flow rate air	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p$ = 0,5 bar)				
Media temperature	-20 °C to +100 °C				
Housing, sleeve, valve	Brass				
Spring, snap ring, balls	stain less steel				
Sealant	NBR				



## Note

Further information on request

## Description

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## ltem

Item							
Identification	Connection	DN	Operating pressure (bar)	Length (mm)	AF (mm)		
K- 07 35 03 81	G 1/8 female	4,3	250,0	48,5	14		
K- 07 35 03 82	G 1/4 female	6,3	200,0	57,6	19		
K- 07 35 03 83	G 3/8 female	7,5	200,0	64,2	22		
K- 07 35 03 84	G 1/2 female	11,0	150,0	76,0	27		
K- 07 35 03 85	G 3/4 female	13,0	100,0	96,0	34		