K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM



Properties				
Operating pressure	See table. All values referred to a medium temperature of 50 °C (static working pressure)			
Flow rate air	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and Δp = 0,5 bar)			
Media temperature	-20 °C to +90 °C			
Housing, sleeve	POM (Delrin), white			
Valve	Stainless steel 1.4305			
Spring, snap ring, balls	stain less steel			
Sealant	NBR			



Note

Further information on request

Description

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Item						
Identification	Connection	Operating pressure (bar)	Length (mm)	DN	AF (mm)	
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14	
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19	
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22	
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27	
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36	