


# K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

**HANSA FLEX**

## Properties

<b>Operating pressure</b>	0 - 35 bar, maximum static working pressure (non-pulsating)
<b>Flow rate air</b>	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Media temperature</b>	-20 °C to +100 °C
<b>Unlocking sleeve</b>	Anodised aluminium
<b>Spring, snap ring, balls</b>	stain less steel
<b>Sealant</b>	NBR



## Note

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. Further information on request

## Description

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Item

Identification	Connection	Colour	Length (mm)	AF (mm)
K- 07 35 06 80	G 1/8 male	green	45,0	14
K- 07 35 06 81	G 1/4 male	green	47,0	17
K- 07 35 06 82	G 1/8 female	green	45,0	14
K- 07 35 06 83	G 1/4 female	green	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	blue	45,0	14
K- 07 35 06 89	G 1/4 male	blue	47,0	17
K- 07 35 06 90	G 1/8 female	blue	45,0	14
K- 07 35 06 91	G 1/4 female	blue	47,0	17
K- 07 35 06 92	G 1/8 male	red	45,0	14
K- 07 35 06 93	G 1/4 male	red	47,0	17
K- 07 35 06 94	G 1/8 female	red	45,0	14
K- 07 35 06 95	G 1/4 female	red	47,0	17