

# K-LKS 7,8 UWB

Stems and plugs DN 7.8

## Properties

<b>Operating pressure</b>	0 - 35 bar, maximum static working pressure (non-pulsating)
<b>Flow rate air</b>	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Media temperature</b>	-20 °C to +100 °C
<b>Material</b>	Brass



## Note

Further information on request

## Item

Identification	Designation	Colour	AF (mm)
K- 07 35 02 71	Stem, I.D. 6	green	-
K- 07 35 02 72	Stem, I.D. 9	green	-
K- 07 35 02 73	Stem, I.D. 6	Brown	-
K- 07 35 02 74	Stem, I.D. 9	Brown	-
K- 07 35 02 75	Stem, I.D. 6	blue	-
K- 07 35 02 76	Stem, I.D. 9	blue	-
K- 07 35 02 77	Stem, I.D. 6	red	-
K- 07 35 02 78	Stem, I.D. 9	red	-
K- 07 35 02 79	Plug G 1/4 male	green	17
K- 07 35 02 80	Plug G 3/8 male	green	19
K- 07 35 02 81	Plug G 1/4 male	Brown	17
K- 07 35 02 82	Plug G 3/8 male	Brown	19
K- 07 35 02 83	Plug G 1/4 male	blue	17
K- 07 35 02 84	Plug G 3/8 male	blue	19
K- 07 35 02 85	Plug G 1/4 male	red	17
K- 07 35 02 86	Plug G 3/8 male	red	19