# HANSA/FLEX

# Properties

Properties	high rigidity of the upper fold Soft, tapered sealing lips Support surfaces on the bottom high suction power optimum damping effect very good adaptation to curved or uneven material
Application	Handling of highly uneven parts (e.g.tubes) \nHandling of highly sensitive parts



## Note

...

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Further information on request

#### Description

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

## Additional information

Attention: The price does not include connection nipples. Please order separately.

Item						
Identification	connection nipple thread external	connection nipple thread internal	overall height with nipple thread external	overall height with nipple thread internal	Ø	
					(mm)	
K- 07 45 00 29	K-07450002 / K-07450004	K-07450007	21 / 22	28	11,0	
K- 07 45 00 31	K-07450002 / K-07450004	K-07450007	21 / 22	28	14,0	
K- 07 45 00 33	K-07450002 / K-07450004	K-07450007	24 / 25	31	16,0	
K- 07 45 00 35	K-07450002 / K-07450004	K-07450007	20,5 / 21,5	27,5	20,0	
K- 07 45 00 37	K-07450004	K-07450007	29	35	25,0	
K- 07 45 00 39	K-07450003	K-07450006	31	42	33,0	
K- 07 45 00 41	K-07450003	K-07450006	32	43	43,0	
K- 07 45 00 43	K-07450003	K-07450006	38	49	53,0	

## Accessories

K-ANSCHLUSSNIP BALGSAUGER Connection nipples for bellows suction pads, round, 1.5 and 2.5 folds