
## K-FEDERSTOESSEL





Properties				
Application	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured			
Temp. min.	0 °C			
Temp. max.	80 °C			
Suctionpad thread	M 3 female			
Design	Spring plunger with high-strength steel rodl, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide			
Spring travel	5,0 mm			



## Note

Further information on request

## Description

Suitable for all round or oval suction pads in our standard range.

Item				
Identification	Vacuum inlet	Length <sub>(mm)</sub>	vertical load (N/m2)	
K- 07 45 00 73	M 3 female	33,5	550	
K- 07 45 00 76	M 5 female	41,2	1500	
K- 07 45 00 74	M 5 female	47,2	1500	
K- 07 45 00 75	M 5 female	59,2	1500	
K- 07 45 00 70	G 1/8 female	80,0	3700	
K- 07 45 00 67	G 1/8 female	95,0	3700	
K- 07 45 00 71	G 1/8 female	93,0	3700	
K- 07 45 00 68	G 1/8 female	124,5	2400	
K- 07 45 00 72	G 1/8 female	124,0	2400	
K- 07 45 00 69	G 1/8 female	154,0	2400	