K-FEDERSTOESSEL
Spring plungers

Properties

Application	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Temp. min.	0 °C
Temp. max.	80 °C
Suctionpad thread	M 3 female
Design	Spring plunger with high-strength steel rodl, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Spring travel	5,0 mm



Note

Further information on request

Description

Suitable for all round or oval suction pads in our standard range.

Item

Identification	Vacuum inlet	Length (mm)	vertical load (N/m2)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.