

K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

HANSA FLEX

Properties

| | |
|------------------------|------------------------------------|
| Media temperature | -5 °C to +80 °C |
| max. shut-off pressure | 16 bar |
| Switching capacity | 5,5 kW |
| Contact type | NC (3-pole) |
| max. operating cycles | 120 (electrical), 600 (mechanical) |
| Protection IP | IP 54 |



Note

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Further information on request

Description

Three-phase version

Ordering information

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Additional information

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Item

| Identification | Pneumatic connection | Adjustment range |
|----------------|----------------------|------------------|
| K- 07 30 24 24 | G 1/2 | 2,0 - 11,0 bar |
| K- 07 30 24 26 | G 1/2 | 2,5 - 16,0 bar |