

# K-DRS STANDARD

## Standard pressure switches

### Properties

<b>Design</b>	Spring-loaded diaphragm (NBR); Spring-loaded piston; (10 to 70 bar versions)
<b>Application</b>	Air, hydraulic oil, oil emulsions, water
<b>Ambient temperature</b>	-25 °C to +85 °C
<b>Electrical connection</b>	Tab connectors 2 x 6.3 x 0.8
<b>Switching frequency</b>	200/min.
<b>Switching voltage</b>	42 V
<b>Material</b>	Galvanised steel



### Note

Further information on request

### Description

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

### Item

Identification	Thread	Adjustment range	Function
K- 07 30 24 94	G 1/8	0,3 - 2,0 bar	closer
K- 07 30 24 95	G 1/8	1,0 - 10,0 bar	closer
K- 07 30 24 96	G 1/8	10,0 - 70,0 bar	closer
K- 07 30 24 97	G 1/4	0,3 - 2,0 bar	closer
K- 07 30 24 98	G 1/4	1,0 - 10,0 bar	closer
K- 07 30 24 99	G 1/4	10,0 - 70,0 bar	closer
K- 07 30 24 10	G 1/8	0,3 - 2,0 bar	opener
K- 07 30 24 11	G 1/8	1,0 - 10,0 bar	opener
K- 07 30 24 12	G 1/8	10,0 - 70,0 bar	opener
K- 07 30 24 13	G 1/4	0,3 - 2,0 bar	opener
K- 07 30 24 14	G 1/4	1,0 - 10,0 bar	opener
K- 07 30 24 15	G 1/4	10,0 - 70,0 bar	opener