

# K-DRS W BAJONETT

Pressure switches - changeover type

## Properties

<b>Design</b>	Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions)
<b>Ambient temperature</b>	-25 °C to +85 °C
<b>Electrical connection</b>	Bayonet coupling connector Ø 2.5 mm
<b>Switching frequency</b>	200/min.
<b>Rated voltage</b>	42 V
<b>Operating principle</b>	Changeover
<b>Material</b>	Galvanised steel



## Note

Further information on request

## Description

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

## Item

Identification	Thread	Adjustment range
K- 07 30 28 36	G 1/8	0,5 - 2,0 bar
K- 07 30 28 37	G 1/8	1,0 - 10,0 bar
K- 07 30 28 38	G 1/8	10,0 - 70,0 bar
K- 07 30 28 39	G 1/4	0,5 - 2,0 bar
K- 07 30 28 40	G 1/4	1,0 - 10,0 bar
K- 07 30 28 41	G 1/4	10,0 - 70,0 bar

## Accessories

**K-WECHSELKONTAKT BANJOETT** Changeover type bayonet coupling