K-DRS W BAJONETT

Pressure switches - changeover type

Properties

Design	Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions)
Ambient temperature	-25 °C to +85 °C
Electrical connection	Bayonet coupling connector Ø 2.5 mm
Switching frequency	200/min.
Rated voltage	42 V
Operating principle	Changeover
Material	Galvanised steel



Note

Further information on request

Description

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

Item

Identification	Thread	Adjustment range
K- 07 30 28 36	G 1/8	0,5 - 2,0 bar
K- 07 30 28 37	G 1/8	1,0 - 10,0 bar
K- 07 30 28 38	G 1/8	10,0 - 70,0 bar
K- 07 30 28 39	G 1/4	0,5 - 2,0 bar
K- 07 30 28 40	G 1/4	1,0 - 10,0 bar
K- 07 30 28 41	G 1/4	10,0 - 70,0 bar

Accessories

K-WECHSELKONTAKT BANJOETT	Changeover type bayonet coupling

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.