

# K-DRS W DREHBAR

Pressure switches, changeover type, turnable

**HANSA FLEX**

## Properties

<b>Design</b>	Spring-loaded diaphragm (NBR)
<b>Application</b>	Air, hydraulic oil, oil emulsions, water
<b>Ambient temperature</b>	-25 °C to +85 °C
<b>Electrical connection</b>	Coupling plug Pg 9, DIN 43650
<b>Switching frequency</b>	200/min.
<b>Rated voltage</b>	250 V
<b>Operating principle</b>	Changeover
<b>Material</b>	Galvanised steel



## Note

Further information on request

## Description

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

## Item

Identification	Thread	Adjustment range
K- 07 30 28 55	G 1/8	0,3 - 2,0 bar
K- 07 30 28 56	G 1/8	1,0 - 10,0 bar
K- 07 30 28 57	G 1/8	10,0 - 70,0 bar
K- 07 30 28 58	G 1/4	0,3 - 2,0 bar
K- 07 30 28 59	G 1/4	1,0 - 10,0 bar
K- 07 30 28 60	G 1/4	10,0 - 70,0 bar