


Properties

Operating pressure	max. 63 bar
Operating temperature	max. 160 °C
Bore	T shaped
Recommended values	Up to 40 °C: 63 bar, 150 °C: 28 bar
Seal	RTFE
Hand lever	Stainless steel
Ball valve	Stainless steel 1.4408



Note

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Further information on request

Description

With T-bore, reduced bore. Version for sealing on all sides with integrated ISO flange plate (ISO 5211). The lever can be turned 360° to allow several switching variants.

Ordering information

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Item

Identification	DN	Thread	A (mm)	B (mm)	L (mm)	Ø D (mm)
K-07 30 15 10	15	G 1/2	114,0	73,0	80,0	12,5
K-07 30 15 11	20	G 3/4	133,0	78,0	87,0	16,0
K-07 30 15 12	25	G 1	133,0	83,0	100,0	20,0
K-07 30 15 13	32	G 1 1/4	187,0	92,0	123,0	25,0
K-07 30 15 14	40	G 1 1/2	187,0	98,0	142,0	31,8
K-07 30 15 15	50	G 2	187,0	126,0	170,0	38,1