


### Properties

<b>Design</b>	Pneumatic actuators, in double- or single acting version, with integrated end-position feedback
<b>Operating pressure</b>	max. 63 bar (depending on temperature and nominal size)
<b>Operating temperature</b>	-20 °C to +70°C
<b>Angle of rotation</b>	90 °
<b>Standardised interfaces</b>	Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S
<b>Pilot pressure</b>	5.5 bar
<b>Valve adapter</b>	Acc. to NAMUR
<b>Drive</b>	aluminium eloxed
<b>Drive seal</b>	NBR
<b>Ball valve</b>	Stainless steel 1.4401, with ISO-flange plate
<b>Ball valve seal</b>	PTFE



### Note

Further information on request

### Description

2-way cock, 3-piece, full bore

### Item

Identification	DN	Thread	A (mm)	B (mm)	D (mm)	L (mm)	AF (mm)
K-07 30 02 42	15	Rp 1/2	133,0	144,0	24,0	75,0	29
K-07 30 02 43	15	Rp 1/2	116,0	135,0	24,0	75,0	29
K-07 30 02 44	20	Rp 3/4	133,0	148,0	27,0	80,0	35
K-07 30 02 45	20	Rp 3/4	116,0	139,0	27,0	80,0	35
K-07 30 02 46	25	Rp 1	133,0	157,0	30,0	90,0	41
K-07 30 02 47	32	Rp 1 1/4	137,0	176,0	37,0	110,0	50
K-07 30 02 48	40	Rp 1 1/2	137,0	186,0	40,0	120,0	58
K-07 30 02 49	50	Rp 2	161,0	207,0	50,0	140,0	74
K-07 30 02 50	65	Rp 2 1/2	180,0	238,0	60,0	185,0	89
K-07 30 02 51	80	Rp 3	209,0	257,0	82,0	205,0	104