


# K-BKR STAN EIN FED VA

Stainless steel ball valves, single-acting actuator - spring to close

**HANSA****FLEX**

## Properties

<b>Design</b>	Pneumatic actuators, in double- or single acting version, with integrated end-position feedback
<b>Operating pressure</b>	max. 63 bar (depending on temperature and nominal size)
<b>Operating temperature</b>	-20 °C to +70°C
<b>Angle of rotation</b>	90 °
<b>Standardised interfaces</b>	Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S
<b>Pilot pressure</b>	5.5 bar
<b>Valve adapter</b>	Acc. to NAMUR
<b>Drive</b>	aluminium eloxed
<b>Drive seal</b>	NBR
<b>Ball valve</b>	Stainless steel 1.4401, with ISO-flange plate
<b>Ball valve seal</b>	PTFE



## Note

Further information on request

## Description

2-way cock, 3-piece, full bore

## Item

Identification	DN	Thread	A (mm)	B (mm)	D (mm)	L (mm)	AF (mm)
K-07 30 02 59	15	Rp 1/2	133,0	144,0	24,0	75,0	29
K-07 30 02 60	15	Rp 1/2	116,0	135,0	24,0	75,0	29
K-07 30 02 61	20	Rp 3/4	133,0	148,0	27,0	80,0	35
K-07 30 02 62	25	Rp 1	137,0	170,0	33,0	90,0	41
K-07 30 02 63	32	Rp 1 1/4	161,0	188,0	37,0	110,0	50
K-07 30 02 64	40	Rp 1 1/2	180,0	198,0	40,0	120,0	58
K-07 30 02 65	50	Rp 2	209,0	224,0	50,0	140,0	74
K-07 30 02 66	65	Rp 2 1/2	221,0	268,0	60,0	185,0	85
K-07 30 02 67	80	Rp 3	221,0	280,0	67,0	205,0	100