
## K-MBKR STELLANTR D MS

Brass ball valves, double-acting actuator



Properties					
Design	Pneumatic actuators, in double- or single acting version, with integrated end-position feedback				
Operating pressure	max. 40 bar (to DN 32); max. 25 bar (from DN 40); max. 16 bar (from DN 65)				
Operating temperature	-20 °C to +70 °C				
Angle of rotation	90 °				
Pilot pressure	5.5 bar				
Valve adapter	Supplied as standard				
Drive	aluminium eloxed				
Drive seal	NBR				
Ball valve	Chrome-plated brass, with ISO-flange plate				
Ball valve seal	PTFE/FKM				
Piloting					





## Note

Further information on request

## Description

2-way cock, full bore

ltem .									
Identification	DN	Thread	А	В	D	L	AF		
			(mm)	(mm)	(mm)	(mm)	(mm)		
K- 07 30 02 00	15	Rp 1/2	133,0	142,0	17,0	75,0	26		
K- 07 30 02 01	15	Rp 1/2	116,0	133,0	17,0	75,0	26		
K- 07 30 02 02	20	Rp 3/4	133,0	145,0	20,0	80,0	32		
K- 07 30 02 03	20	Rp 3/4	116,0	136,0	20,0	80,0	32		
K- 07 30 02 04	25	Rp 1	133,0	148,0	25,0	90,0	41		
K- 07 30 02 05	25	Rp 1	116,0	139,0	25,0	90,0	41		
K- 07 30 02 06	32	Rp 1 1/4	116,0	150,0	30,0	110,0	50		
K- 07 30 02 07	40	Rp 1 1/2	133,0	166,0	36,0	120,0	55		
K- 07 30 02 08	50	Rp 2	137,0	191,0	45,0	140,0	70		
K- 07 30 02 09	65	Rp 2 1/2	161,0	213,0	57,0	155,0	83		
K- 07 30 02 10	80	Rp 3	161,0	225,0	68,0	182,0	98		