
K-3 BKR STELLANTR E L MS

Brass ball valves, 3-way, with single-acting actuator, L-bore



Properties						
Design	Pneumatic actuators, in double- or single acting version, with integrated end-position feedback					
Bore	L shaped					
Operating temperature	-20 °C to +70 °C					
Angle of rotation	90 °					
Pilot pressure	5.5 bar					
Valve adapter	Supplied as standard					
Drive	aluminium eloxed					
Drive seal	NBR					
Ball valve	Chrome-plated brass, with ISO-flange plate					
Ball valve seal	PTFE/FKM					





Note

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211) Further information on request

Description

3-way cock, L-bore, full bore

Additional information

Other T-positions on request

item										
Identification	DN	Thread	Position	PN (bar)	Α	В	D	L	AF	
					(mm)	(mm)	(mm)	(mm)	(mm)	
K- 07 30 02 90	15	Rp 1/2	L	40	133,0	142,0	20,0	64,5	25	
K- 07 30 02 91	25	Rp 1	L	40	133,0	150,5	30,0	97,0	41	
K- 07 30 02 92	40	Rp 1 1/2	L	25	180,0	193,5	43,0	135,0	55	