

# K-RD DURCHGANGSFORM

Unidirectional valves

**HANSA FLEX**

## Properties

|                            |  |
|----------------------------|--|
| <b>Operating pressure</b>  | Max. 16 bar  |
| <b>Media temperature</b>   | max. +180 °C   |
| <b>Opening pressure</b>    | min. 0.4 to 0.5 bar (size G 1/4 to 1/2 inch); min. 0.1 bar (for size 3/4 to G 1) |
| <b>Ambient temperature</b> | Max. +180 °C   |
| <b>Sealant</b>             | FKM  |
| <b>Housing</b>             | Brass  |



## Note

Further information on request

## Item

| Identification | Thread       | Length<br>(mm) | AF<br>(mm) |
|----------------|--------------|----------------|------------|
| K- 07 30 24 48 | G 1/4 female | 53,0           | 19         |
| K- 07 30 24 49 | G 3/8 female | 54,0           | 19         |
| K- 07 30 24 50 | G 1/2 female | 63,0           | 24         |
| K- 07 30 24 51 | G 3/4 female | 58,0           | 36         |
| K- 07 30 24 52 | G 1 female   | 68,5           | 46         |
| K- 07 30 24 43 | G 1/4 male   | 53,5           | 19         |
| K- 07 30 24 44 | G 3/8 male   | 54,0           | 19         |
| K- 07 30 24 45 | G 1/2 male   | 68,0           | 24         |
| K- 07 30 24 46 | G 3/4 male   | 77,0           | 36         |
| K- 07 30 24 47 | G 1 male     | 82,0           | 46         |