
K-RD DURCHGANGSFORM

Unidirectional valves



| Properties | | | |
|---------------------|--|--|--|
| Operating pressure | Max. 16 bar | | |
| Media temperature | max. +180 °C | | |
| Opening pressure | min. 0.4 to 0.5 bar (size G 1/4 to 1/2 inch); min. 0.1 bar (for size 3/4 to G 1) | | |
| Ambient temperature | Max. +180 °C | | |
| Sealant | FKM | | |
| Housing | Brass | | |



Note

Further information on request

| Item | | | | |
|----------------|--------------|----------------|------------|--|
| Identification | Thread | Length (mm) | AF (mm) | |
| K- 07 30 24 48 | G 1/4 female | 53,0 | 19 | |
| K- 07 30 24 49 | G 3/8 female | 54,0 | 19 | |
| K- 07 30 24 50 | G 1/2 female | 63,0 | 24 | |
| K- 07 30 24 51 | G 3/4 female | 58,0 | 36 | |
| K- 07 30 24 52 | G 1 female | 68,5 | 46 | |
| K- 07 30 24 43 | G 1/4 male | 53,5 | 19 | |
| K- 07 30 24 44 | G 3/8 male | 54,0 | 19 | |
| K- 07 30 24 45 | G 1/2 male | 68,0 | 24 | |
| K- 07 30 24 46 | G 3/4 male | 77,0 | 36 | |
| K- 07 30 24 47 | G 1 male | 82,0 | 46 | |