


K-RD FORM VOLLER DURCHGANG

Unidirectional valves



Properties

| | |
|-----------------------|--------------------------------|
| Operating temperature | -20 °C to +100 °C |
| Thread description | G thread acc. DIN EN ISO 228-1 |
| Opening pressure | 0.2 - 0.4 bar |
| Seals | NBR |
| Spring | Stainless-steel |
| Housing | Brass |
| Valve pin | Brass |
| Valve disc | Stainless steel |



Note

Further information on request

| Item | | | | |
|----------------|---------|----------------|--------------------------------|------------|
| Identification | Thread | Length (mm) | Max. working pressure (bar) | AF (mm) |
| K- 07 30 24 60 | G 3/8 | 54,0 | 25 | 23 |
| K- 07 30 24 61 | G 1/2 | 57,0 | 25 | 27 |
| K- 07 30 24 62 | G 3/4 | 64,0 | 25 | 33 |
| K- 07 30 24 63 | G 1 | 74,5 | 25 | 40 |
| K- 07 30 24 64 | G 1 1/4 | 82,0 | 18 | 50 |
| K- 07 30 24 65 | G 1 1/2 | 93,0 | 18 | 55 |
| K- 07 30 24 66 | G 2 | 100,0 | 18 | 70 |