# K-RD FORM VOLLER DURCHGANG

Unidirectional valves

## Properties

| | |
|---|---|
| **Operating temperature** | -20 °C to +100 °C |
| **Thread description** | G thread acc. DIN EN ISO 228-1 |
| **Opening pressure** | 0.2 - 0.4 bar |
| **Seals** | NBR |
| **Spring** | Stainless-steel |
| **Housing** | Brass |
| **Valve pin** | Brass |
| **Valve disc** | Stainless steel |



## Note

Further information on request

## Item

| Identification | Thread | Length (mm) | Max. working pressure (bar) | AF (mm) |
|---|---|---|---|---|
| **K- 07 30 24 60** | G 3/8 | 54,0 | 25 | 23 |
| **K- 07 30 24 61** | G 1/2 | 57,0 | 25 | 27 |
| **K- 07 30 24 62** | G 3/4 | 64,0 | 25 | 33 |
| **K- 07 30 24 63** | G 1 | 74,5 | 25 | 40 |
| **K- 07 30 24 64** | G 1 1/4 | 82,0 | 18 | 50 |
| **K- 07 30 24 65** | G 1 1/2 | 93,0 | 18 | 55 |
| **K- 07 30 24 66** | G 2 | 100,0 | 18 | 70 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*