# K-SCHMUTZFAENGER ROTGUSS

Strainers

# HANSA/FLEX

## Properties

110001100	
Operating pressure	Max. 16 bar
Operating temperature	-15 °C to +150 °C
Screen	Double stainless steel screen for fine filtration, mesh size 0.25 mm
Housing	Bronze
Head piece	Brass
Seals	FKM (FPM) O-ring





#### Note

Further information on request

### Description

For liquids, gases, steam, water, mineral, fuel and hydraulic oils, fuels and othernon-corrosive media in a liquid or gaseous state.

Item							
Identification	DN	Thread	C (mm)	L (mm)	AF1 (mm)	AF2 (mm)	
K- 07 30 25 08	8	G 1/4	34,0	56,0	21	17	
K- 07 30 25 09	10	Rp 3/8	34,0	63,5	22	17	
K- 07 30 25 10	15	Rp 1/2	42,0	66,5	27	22	
K- 07 30 25 11	20	Rp 3/4	52,0	76,5	32	27	
K- 07 30 25 12	25	G 1	61,0	90,0	38	32	
K- 07 30 25 13	32	G 1 1/4	73,0	112,0	47	41	
K- 07 30 25 14	40	G 1 1/2	82,0	120,0	54	46	
K- 07 30 25 15	50	G 2	94,0	150,0	66	56	