

# K-XV 6-KANT

Double nipples, hexagonal

## Properties

|                         |                              |
|-------------------------|------------------------------|
| <b>Working pressure</b> | Max. 20 bar                  |
| <b>Male thread</b>      | Parallel to DIN EN ISO 228-1 |
| <b>Material</b>         | Stainless steel 1.4408       |



## Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Further information on request

## Item

| Identification | Thread  | L1<br>(mm) | L2<br>(mm) | AF    |
|----------------|---------|------------|------------|-------|
| K- 07 40 12 18 | G 1/8   | 30,0       | 12,0       | 13 mm |
| K- 07 40 12 19 | G 1/4   | 32,0       | 13,0       | 16 mm |
| K- 07 40 12 20 | G 3/8   | 34,0       | 13,0       | 20 mm |
| K- 07 40 12 21 | G 1/2   | 37,5       | 15,0       | 24 mm |
| K- 07 40 12 22 | G 3/4   | 46,0       | 18,0       | 29 mm |
| K- 07 40 12 23 | G 1     | 51,0       | 19,0       | 35 mm |
| K- 07 40 12 24 | G 1 1/4 | 57,0       | 22,0       | 46 mm |
| K- 07 40 12 25 | G 1 1/2 | 58,0       | 23,0       | 51 mm |
| K- 07 40 12 26 | G 2     | 66,9       | 26,0       | 63 mm |