# K-KM
Hexagonal lock nuts

## Properties

| | |
|---|---|
| **Working pressure** | Max. 20 bar |
| **Female thread** | Parallel to DIN EN ISO 228-1 |
| **Material** | Stainless steel 1.4408 |



## Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Further information on request

## Item

| Identification | Thread | L1 (mm) | AF |
|---|---|---|---|
| **K- 07 40 38 78** | G 1/8 | 6,2 | 14 mm |
| **K- 07 40 38 79** | G 1/4 | 7,2 | 22 mm |
| **K- 07 40 38 80** | G 3/8 | 8,0 | 27 mm |
| **K- 07 40 38 81** | G 1/2 | 9,5 | 32 mm |
| **K- 07 40 38 82** | G 3/4 | 9,8 | 36 mm |
| **K- 07 40 38 83** | G 1 | 10,4 | 46 mm |
| **K- 07 40 38 84** | G 1 1/4 | 11,0 | 55 mm |
| **K- 07 40 38 85** | G 1 1/2 | 12,3 | 60 mm |
| **K- 07 40 38 86** | G 2 | 13,0 | 74 mm |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*