# K-VERSCHLUSSKAPPEN 6KT U. 8KT

Caps, hexagonal (G 3/4 to G 2 = octagon)

HANSA-FLEX

## Properties

| | |
|---|---|
| **Working pressure** | Max. 20 bar |
| **Female thread** | Parallel to DIN EN ISO 228-1 |
| **Material** | Stainless steel 1.4408 |



## Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Further information on request

## Item

| Identification | Thread | L1 (mm) | AF |
|---|---|---|---|
| **K- 07 40 39 40** | G 1/8 | 15,5 | 13 mm |
| **K- 07 40 39 41** | G 1/4 | 16,0 | 16 mm |
| **K- 07 40 39 42** | G 3/8 | 18,0 | 20 mm |
| **K- 07 40 39 43** | G 1/2 | 22,6 | 26 mm |
| **K- 07 40 39 44** | G 3/4 | 25,0 | 32 mm |
| **K- 07 40 39 45** | G 1 | 30,0 | 40 mm |
| **K- 07 40 39 46** | G 1 1/4 | 31,0 | 48 mm |
| **K- 07 40 39 47** | G 1 1/2 | 33,0 | 56 mm |
| **K- 07 40 39 48** | G 2 | 36,0 | 66 mm |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*