
## K-INLINE-DRG IG M SEKUNDAERENTLUEFT

Inline pressure regulators, 2 x female thread, self-relieving



Properties	
Operating pressure	Max. 25 bar
Temp. range	0 °C to +80 °C
Housing	Aluminium
Other parts	Stainless steel, nitrile rubber, brass





## Note

Further information on request

## Description

Item					
Identification	Thread	Working pressure (preset)	flow rate	A (mm)	AF (mm)
K- 07 25 02 83	G 1/4	2 bar	600 - 800 l/min	56,6	16
K- 07 25 02 84	G 1/4	3 bar	600 - 800 l/min	56,6	16
K- 07 25 02 85	G 1/4	4 bar	600 - 800 l/min	56,6	16
K- 07 25 02 86	G 1/4	5 bar	600 - 800 l/min	56,6	16
K- 07 25 02 87	G 1/4	6 bar	600 - 800 l/min	56,6	16
K- 07 25 02 88	G 1/4	8 bar	600 - 800 l/min	56,6	16
K- 07 25 02 89	G 3/8	2 bar	2000 I/min	63,0	22
K- 07 25 02 90	G 3/8	4 bar	2000 I/min	63,0	22
K- 07 25 02 91	G 3/8	6 bar	2000 I/min	63,0	22
K- 07 25 02 92	G 3/8	8 bar	2000 I/min	63,0	22
	·	<u> </u>			
K- 07 25 02 93	G 1/2	2 bar	3000 l/min	67,5	27
K- 07 25 02 94	G 1/2	4 bar	3000 l/min	67,5	27
K- 07 25 02 95	G 1/2	6 bar	3000 l/min	67,5	27
K- 07 25 02 96	G 1/2	8 bar	3000 l/min	67,5	27

13.12.2025 HANSA-FLEX AG www.hansa-flex.com