

K-GE AGR-K

Male stud couplings, polyamide, conical male thread acc. to ISO 7-1

HANSA FLEX

Properties

Temp. range -40 °C to +90 °C



Note

Further information on request

Description

Lightweight tube connectors distinguished by high strength, toughness, resistance to abrasion and impact resistance. Resistant to: Acetone, benzene, benzene, butane, alcohols, diesel fuels, crude oil, natural gas, ethanol, fruit juices, glycerine, fuel oil, hydraulic fluids, aliphatic ketones, carbon dioxide, carbonic acid, engine oils, methanol, propane, liquefied gas, lubricating oils, lubricating greases, town gas, washing liquor and water.

Item	Identification	Thread	for hose	L1 (mm)	max. permissible overpressure (bar)	AF
	K- 07 40 16 63	M 5	LW 3 mm	19,5	10	6 mm
	K- 07 40 16 64	R 1/8	LW 4 mm	27,0	10	10 mm
	K- 07 40 16 65	R 1/8	LW 6 mm	32,5	10	10 mm
	K- 07 40 16 66	R 1/8	LW 8 mm	38,0	10	14 mm
	K- 07 40 16 67	R 1/4	LW 4 mm	32,0	10	14 mm
	K- 07 40 16 68	R 1/4	LW 5 mm	36,0	10	14 mm
	K- 07 40 16 69	R 1/4	LW 6 mm	37,5	10	14 mm
	K- 07 40 16 70	R 1/4	LW 8 mm	41,0	10	14 mm
	K- 07 40 16 71	R 1/4	LW 10 mm	43,5	10	14 mm
	K- 07 40 16 72	R 3/8	LW 6 mm	39,0	10	17 mm
	K- 07 40 16 73	R 3/8	LW 8 mm	41,0	10	17 mm
	K- 07 40 16 74	R 3/8	LW 10 mm	43,5	10	17 mm
	K- 07 40 16 75	R 3/8	LW 12 mm	45,5	10	17 mm
	K- 07 40 16 76	R 1/2	LW 8 mm	49,0	10	22 mm
	K- 07 40 16 77	R 1/2	LW 12 mm	54,0	10	22 mm
	K- 07 40 16 78	R 1/2	LW 16 mm	58,0	10	22 mm
	K- 07 40 46 50	R 3/4	LW 16 mm	58,0	10	27 mm
	K- 07 40 46 51	R 3/4	LW 19 mm	58,0	10	27 mm
	K- 07 40 46 52	R 1	LW 25 mm	69,0	10	32 mm