


Properties

Working pressure Max. 20 bar

Material Stainless steel 1.4571



Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.

Further information on request

Additional information

Further types and dimensions on request.

Item	Identification	Thread 1	Thread 2	L1 (mm)	L2 (mm)	AF
K-07 40 11 98		M 5	M 5	13,0	8,0	7 mm
K-07 40 11 99		M 5	G 1/8	17,0	12,0	14 mm
K-07 40 12 00		M 5	G 1/4	21,0	14,0	17 mm
K-07 40 11 95		G 1/8	G 1/8	21,0	13,0	14 mm
K-07 40 11 97		G 1/8	G 1/4	22,0	14,0	17 mm
K-07 40 11 96		G 1/8	G 3/8	25,0	16,0	19 mm
K-07 40 12 01		G 1/4	G 1/4	23,0	14,0	17 mm
K-07 40 12 03		G 1/4	G 3/8	24,0	15,0	19 mm
K-07 40 12 02		G 1/4	G 1/2	27,0	18,0	24 mm
K-07 40 12 04		G 3/8	G 3/8	25,0	15,0	19 mm
K-07 40 12 06		G 3/8	G 1/2	27,0	17,0	24 mm
K-07 40 12 05		G 3/8	G 3/4	36,0	24,0	32 mm
K-07 40 12 07		G 1/2	G 1/2	29,0	17,0	24 mm
K-07 40 12 09		G 1/2	G 3/4	33,0	21,0	32 mm
K-07 40 12 08		G 1/2	G 1	40,0	24,0	36 mm
K-07 40 12 12		G 3/4	G 3/4	33,0	21,0	32 mm
K-07 40 12 10		G 3/4	G 1	40,0	24,0	36 mm
K-07 40 12 11		G 1	G 1	42,0	26,0	36 mm