



# K-XV AGM MS NI

Double nipples, parallel male thread, nickel-plated brass

**HANSA FLEX**

## Properties

Operating temperature	Max. 150 °C
Pressure	Max. 60 bar
Material	Nickel-plated brass



## Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Further information on request

## Description

Suitable for air, water, oil, steam, etc.

## Additional information

Further types and dimensions on request.

Item	Thread 1	Thread 2	L1 (mm)	L2 (mm)	L3 (mm)	AF
K- 07 40 12 80	M 5	M 5	11,5	4,0	4,0	8 mm
K- 07 40 12 81	M 5	G 1/8	14,5	6,0	4,0	14 mm
K- 07 40 12 82	G 1/8	G 1/8	17,0	6,0	6,0	14 mm
K- 07 40 12 83	G 1/8	G 1/4	19,0	8,0	6,0	17 mm
K- 07 40 12 84	G 1/8	G 3/8	20,0	9,0	6,0	20 mm
K- 07 40 12 85	G 1/4	G 1/4	21,0	8,0	8,0	17 mm
K- 07 40 12 86	G 1/4	G 3/8	22,0	9,0	8,0	20 mm
K- 07 40 12 87	G 1/4	G 1/2	24,0	10,0	8,0	25 mm
K- 07 40 12 88	G 3/8	G 3/8	24,0	9,0	9,0	20 mm
K- 07 40 12 89	G 3/8	G 1/2	25,5	10,0	9,0	25 mm
K- 07 40 45 02	G 3/8	G 3/4	27,0	12,0	9,0	27 mm
K- 07 40 12 90	G 1/2	G 1/2	26,5	10,0	10,0	25 mm
K- 07 40 12 91	G 1/2	G 3/4	27,5	11,0	10,0	30 mm
K- 07 40 45 03	G 1/2	G 1	32,5	15,0	10,5	34 mm
K- 07 40 12 93	G 3/4	G 3/4	28,0	11,0	11,0	30 mm
K- 07 40 12 92	G 3/4	G 1	30,0	11,0	12,0	36 mm
K- 07 40 12 94	G 1	G 1	31,0	12,0	12,0	36 mm
K- 07 40 45 04	G 1	G 1 1/4	38,0	16,0	15,0	43 mm
K- 07 40 45 05	G 1	G 1 1/2	38,5	16,0	15,0	50 mm
K- 07 40 45 06	G 1	G 2	42,0	18,0	15,0	60 mm
K- 07 40 45 07	G 1 1/4	G 1 1/4	39,0	16,0	16,0	42 mm
K- 07 40 45 08	G 1 1/4	G 1 1/2	40,0	16,0	16,0	50 mm
K- 07 40 45 09	G 1 1/4	G 2	43,0	18,0	16,0	60 mm
K- 07 40 45 10	G 1 1/2	G 1 1/2	39,5	16,0	16,0	50 mm
K- 07 40 45 11	G 1 1/2	G 2	44,5	18,0	17,5	60 mm
K- 07 40 45 12	G 2	G 2	44,0	17,5	17,5	60 mm
K- 07 40 45 13	G 2	G 2 1/2	54,0	24,0	19,0	77 mm
K- 07 40 45 14	G 2	G 3	50,0	20,0	20,0	89 mm
K- 07 40 45 15	G 2 1/2	G 2 1/2	59,0	24,0	24,0	77 mm
K- 07 40 45 16	G 2 1/2	G 3	52,5	20,0	22,5	89 mm
K- 07 40 45 17	G 3	G 3	60,0	24,5	24,5	89 mm