
K-PROP REGELVE SENTRONIC D

Proportional control valves, digital, 24 VDC



0 - 60 °C
0 - 50 °C
Air or neutral gases (≤ 50 µm filter specified)
0 - 10 bar
0 to 10 V (on request: 0 to 20 mA or 4 to 20 mA)
0 - 10 V
0 - 10 V
Proportional solenoid valve
Pressure switch output PNP +/- 5%
Pressure relieved in case of loss of voltage
POM
NBR
Aluminium





Note

Further information on request

Description

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital. <a href="https://document.org/repressure-negative-ne

Item					
Identification	Connection	DN	Flow rate	В	C
			(L/min)		(mm)
K- 07 25 10 04	G 1/8	4	780	52.0 mm	112,0
K- 07 25 10 05	G 1/4	4	780	52.0 mm	112,0
K- 07 25 10 06	G 1/4	8	1750	66.0 mm	138,0
K- 07 25 10 07	G 3/8	8	1750	66.0 mm	138,0