## K-STECKERVERSTAERKER

Plug amplifier (mounting directly on the valve)



Properties	
Rated voltage	24 V DC
Temp. range	-10 °C to +75 °C (plug amplifier), -10 °C to +60 °C (chopper amplifier)
Housing	PA



## Note

Further information on request

## **Description**

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital. <a href="https://document.com/stepless-adjustment">https://document.com/stepless-adjustment of these parameters is vital.</a><a href="https://document.com/stepless-adjustment">https://document.com/stepless-adjustment of these parameters is vital.</a><a href="https://document.com/stepless-adjustment-of-these parameters is vital.">https://document.com/stepless-adjustment-of-these parameters is vital.</a><a href="https://document.com/stepless-adjustment-of-these parameters is vital.">https://document.com/stepless-adjustment-of-these parameters is vital.</a><a href="https://document.com/stepless-adjustment-of-these parameters is vital.">https://document-of-these parameters is vital.</a><a href="https://document-of-these parameters-of-these par

Item		
Identification	for devices with connection	
K- 07 25 09 99	G 1/8	
K- 07 25 10 00	G 1/4 , G 3/8	